






**4251 N.E. Port Drive
Lee's Summit, MO 64064
800-554-8268**



124, 124/1



**128, 128/1
134, 134/3, 134VLR, 134/3VLR, 134C**



**144, 144/3
154, 154/3**



Owner & Assembly Manual

Les Spécifications Françaises Enclos

Table Of Contents

3	Welcome
4 - 6	154 and 154/3 12^{MINUTE} Specifications/Exposure Schedule
7 -9	154 and 154/3 15^{MINUTE} Specifications/Exposure Schedule
10 - 12	144 and 144/3 Specifications/Exposure Schedule
13 - 15	134 and 134/3 Specifications/Exposure Schedule
16 - 18	134VLR and 134/3VLR Specifications/Exposure Schedule
19 - 21	134C Specifications/Exposure Schedule
22 - 24	128 and 128/1 Specifications/Exposure Schedule
25 - 27	124 and 124/1 Specifications/Exposure Schedule
28	Warnings And Cautions
29	Repairs
29	Service
29	Replacement Parts And Lamps
29	Eye Protection
30	Care And Cleaning
31	Relamping
32 - 33	Facial Relamping
34 - 41	Timer System
42 - 54	154, 154/3, 144 and 144/3 Assembly Instructions
55 - 63	134, 134/3, 134VLR, 134/3VLR, 134C, 128 and 128/1 Assembly Instructions
64 - 70	124 and 124/1 Assembly Instructions
71	Limited Warranty

Welcome

Dear Valued Customer:

Congratulations! You have just purchased one of the finest pieces of tanning equipment available to the indoor tanning industry. We at Heartland Tanning, Inc. sincerely appreciate your business.

The America's best tan™ line is manufactured right here in the heart of our country. Our tanning beds are constructed of 12GAUGE solid steel and are designed to hold up under heavy use. We have confidence in our beds and that is why our entire tanning bed line is backed by Heartland's unprecedented 3 year limited warranty. Designed to be user friendly, the beds are easy to assemble and easy to maintain.

Please read your owner & assembly manual thoroughly prior to the first use of your new tanning bed.

Heartland Tanning, Inc.
4251 N.E. Port Drive
Lee's Summit, MO 64064
1-800-554-8268

America's best tan™

NOTICE: Any misuse, abuse, modifications, alteration, improper installation, etc. of this product or its intended use will subject said party to direct responsibility for any and all consequences resulting from such action. Furthermore, such actions will void all warranties and may relieve Heartland Tanning, Inc. of any liabilities relating to said product.

SPECIFICATIONS 154 and 154/3 - 12 MINUTE

154

LENGTH:	87.5"L X 51"W
WEIGHT:	850LBS
NUMBER OF LAMPS:	44
ELECTRICAL DRAW:	35AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

154/3

LENGTH:	87.5"L X 51"W
WEIGHT:	865LBS
NUMBER OF LAMPS:	44, 3 facial lamps
ELECTRICAL DRAW:	39AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 154 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session. Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 154 and 154/3 - 12 MINUTE

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Cosmolux VHR 16180/160W lamps and Hi-Tan 10198/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable).

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	2MINUTES	3MINUTES	5MINUTES	9MINUTES	12MINUTES
III - Average	2MINUTES	3MINUTES	5MINUTES	9MINUTES	12MINUTES
IV - Brown	2MINUTES	5MINUTES	7MINUTES	11MINUTES	12MINUTES
V - Dark Brown	2MINUTES	5MINUTES	7MINUTES	12MINUTES	12MINUTES
MAXIMUM EXPOSURE TIME IS 12 MINUTES This product is in comformity with performace standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Cosmolux VHR 16180/160W lamps and Hi-Tan 10198/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable).** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques - 12 MINUTE

154 - 12 Minute

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 44
 aspiration électrique : 35 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

154/3 - 12 Minute

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 47
 aspiration électrique : 39 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Cosmolux VHR 16180/160W, Hi-Tan 10198/100W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable).** La position minimum d'exposition est à 0,5 pouces (1,27 cm) de la surface de la lampe (instituez par le manufacturier). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	2 MINUTES	3 MINUTES	5 MINUTES	9 MINUTES	12 MINUTES
III – Moyen	2 MINUTES	3 MINUTES	5 MINUTES	9 MINUTES	12 MINUTES
IV – Foncé	2 MINUTES	5 MINUTES	7 MINUTES	11 MINUTES	12 MINUTES
V – Très foncé	2 MINUTES	5 MINUTES	7 MINUTES	12 MINUTES	12 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 12 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS 154 and 154/3 - 15 MINUTE

154

LENGTH:	87.5"L X 51"W
WEIGHT:	850LBS
NUMBER OF LAMPS:	44
ELECTRICAL DRAW:	35AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

154/3

LENGTH:	87.5"L X 51"W
WEIGHT:	865LBS
NUMBER OF LAMPS:	44, 3 facial lamps
ELECTRICAL DRAW:	39AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 154 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session. Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 154 and 154/3 - 15 MINUTE

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Cosmolux VHR 16180/160W lamps and Cosmolux VLR 16180/160W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable).

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	3MINUTES	6MINUTES	8MINUTES	10MINUTES	15MINUTES
III - Average	3MINUTES	6MINUTES	8MINUTES	10MINUTES	15MINUTES
IV - Brown	3MINUTES	8MINUTES	10MINUTES	15MINUTES	15MINUTES
V - Dark Brown	3MINUTES	8MINUTES	10MINUTES	15MINUTES	15MINUTES
MAXIMUM EXPOSURE TIME IS 15 MINUTES					
This product is in comformity with performace standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Cosmolux VHR 16180/160W lamps and Cosmolux VLR 16180/160W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable).** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques - 15 MINUTE

154 - 15 Minute

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 44
 aspiration électrique : 35 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

154/3 - 15 Minute

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 47
 aspiration électrique : 39 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Cosmolux VHR 16180/160W, Cosmolux VLR 16180/160W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable).** La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	3 MINUTES	6 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES
III – Moyen	3 MINUTES	6 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES
IV – Foncé	3 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES	15 MINUTES
V – Très foncé	3 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES	15 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 15 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					

SPECIFICATIONS

144

LENGTH:	87.5"L X 51"W
WEIGHT:	850LBS
NUMBER OF LAMPS:	44
ELECTRICAL DRAW:	35AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

144/3

LENGTH:	87.5"L X 51"W
WEIGHT:	865LBS
NUMBER OF LAMPS:	44, 3 facial lamps
ELECTRICAL DRAW:	39AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 50AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 144 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

- SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
- SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
- SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
- SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 144 and 144/3

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Bellarium SR RA1-12/160W lamps, Everglo 71"/100W lamps, Bellarium S SA1 71/100W or Durasun F71BP 100W, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (facial unit, where applicable).

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
III - Average	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
IV - Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
V - Dark Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
MAXIMUM EXPOSURE TIME IS 20 MINUTES This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Bellarium SR RA1-12/160W lamps, Everglo 71"/100W lamps, Bellarium S SA 71/100W or Dura Sun F71BP 100W, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable).** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

144

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 44
 aspiration électrique : 35 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

144/3

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 865 livres
 nombre de lampes : 47
 aspiration électrique : 39 ampères à 220 volts
 circuit requis : 220 volts, double poteau, briseur de 50 ampères, avec disjoncteur différentiel, briseur de 20 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Bellarium SR RA1-12"/160W et Everglo 71"/100W et Bellarium S SA1 71/100W et Dura Sun F71BP 100W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable).** La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
III – Moyen	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
IV – Foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
V – Très foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 20 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS

134

LENGTH:	87.5"L X 42.5"W
WEIGHT:	720LBS
NUMBER OF LAMPS:	34
ELECTRICAL DRAW:	23AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

134/3

LENGTH:	87.5"L X 42.5"W
WEIGHT:	750LBS
NUMBER OF LAMPS:	34, 3 facial lamps
ELECTRICAL DRAW:	26AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 134 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 134 and 134/3

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Everglo 71"/100W lamps, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (facial unit, where applicable)].

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
III - Average	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
IV - Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
V - Dark Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
MAXIMUM EXPOSURE TIME IS 20 MINUTES					
This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Everglo 71"/100W lamps, Durasun F71 BP 100W, Bellarium S SA1 71/100W and [Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)].** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

134

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 720 livres
 nombre de lampes : 34
 aspiration électrique : 23 ampères à 220 volts
 circuit requis : 220 volts, avec un disjoncteur
 différentiel, briseur de 50 ampères

134/3

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 750 livres
 nombre de lampes : 37
 aspiration électrique : 26 ampères à 220 volts
 circuit requis : 220 volts, avec un disjoncteur
 différentiel, briseur de 50 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Everglow 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W et [Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable)]**. La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
III – Moyen	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
IV – Foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
V – Très foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 20 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS

134 VLR

LENGTH:	87.5"L X 42.5"W
WEIGHT:	720LBS
NUMBER OF LAMPS:	34
ELECTRICAL DRAW:	23AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

134/3 VLR

LENGTH:	87.5"L X 42.5"W
WEIGHT:	750LBS
NUMBER OF LAMPS:	34, 3 facial lamps
ELECTRICAL DRAW:	26AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 134 VLR is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

- SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
- SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
- SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
- SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 134 VLR and 134/3 VLR

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Cosmolux VLR 18810/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (facial unit, where applicable).

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	3MINUTES	6MINUTES	8MINUTES	10MINUTES	15MINUTES
III - Average	3MINUTES	6MINUTES	8MINUTES	10MINUTES	15MINUTES
IV - Brown	3MINUTES	8MINUTES	10MINUTES	15MINUTES	15MINUTES
V - Dark Brown	3MINUTES	8MINUTES	10MINUTES	15MINUTES	15MINUTES
MAXIMUM EXPOSURE TIME IS 15 MINUTES					
This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Cosmolux VLR 18810/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)].** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

134 VLR

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 720 livres
 nombre de lampes : 34
 aspiration électrique : 23 ampères à 220 volts
 circuit requis : 220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

134/3 VLR

longueur : 87,5 pouces par 51 pouces
 hauteur : 41 pouces (avec le couvercle fermé)
 poids d'expédition : 750 livres
 nombre de lampes : 37
 aspiration électrique : 26 ampères à 220 volts
 circuit requis : 220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Cosmolux VLR 18810/100W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable).**

La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le manufacturier). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	3 MINUTES	6 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES
III – Moyen	3 MINUTES	6 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES
IV – Foncé	3 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES	15 MINUTES
V – Très foncé	3 MINUTES	8 MINUTES	10 MINUTES	15 MINUTES	15 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 15 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS

134C

LENGTH:	87.5"L X 42.5"W
WEIGHT:	720LBS
NUMBER OF LAMPS:	34
ELECTRICAL DRAW:	23AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 134C is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

- SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
- SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
- SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
- SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 134C

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Cosmostar Longlife 12503/100W lamps.

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	5MINUTES	10MINUTES	20MINUTES	30MINUTES	30MINUTES
III - Average	5MINUTES	10MINUTES	20MINUTES	30MINUTES	30MINUTES
IV - Brown	7MINUTES	15MINUTES	30MINUTES	30MINUTES	30MINUTES
V - Dark Brown	7MINUTES	15MINUTES	30MINUTES	30MINUTES	30MINUTES
MAXIMUM EXPOSURE TIME IS 30 MINUTES					
This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Cosmostar Longlife 12503/100W lamps.** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow.

CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

134C

longueur :	87,5 pouces par 51 pouces
hauteur :	41 pouces (avec le couvercle fermé)
poids d'expédition :	720 livres
nombre de lampes :	34
aspiration électrique :	23 ampères à 220 volts
circuit requis :	220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Cosmostar Longlife 12503/100W**. La position minimum d'exposition est à 0,5 pouces (1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	5 MINUTES	10 MINUTES	20 MINUTES	30 MINUTES	30 MINUTES
III – Moyen	5 MINUTES	10 MINUTES	20 MINUTES	30 MINUTES	30 MINUTES
IV – Foncé	7 MINUTES	15 MINUTES	30 MINUTES	30 MINUTES	30 MINUTES
V – Très foncé	7 MINUTES	15 MINUTES	30 MINUTES	30 MINUTES	30 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 30 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS

128

LENGTH:	87.5"L X 42.5"W
WEIGHT:	630LBS
NUMBER OF LAMPS:	28
ELECTRICAL DRAW:	18AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

128/1

LENGTH:	87.5"L X 42.5"W
WEIGHT:	640LBS
NUMBER OF LAMPS:	28, 1 facial lamp
ELECTRICAL DRAW:	23AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 128 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 128 and 128/1

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Everglo 71"/100W lamps, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (facial unit, where applicable)].

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
III - Average	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
IV - Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
V - Dark Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
MAXIMUM EXPOSURE TIME IS 20 MINUTES					
This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Everglo 71"/100W lamps, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps Heraeus E-400 HPT lamps (Facial unit, where applicable)].** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

128

longueur :	87,5 pouces par 51 pouces
hauteur :	41 pouces (avec le couvercle fermé)
poids d'expédition :	630 livres
nombre de lampes :	28
aspiration électrique :	18 ampères à 220 volts
circuit requis :	220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

128/1

longueur :	87,5 pouces par 51 pouces
hauteur :	41 pouces (avec le couvercle fermé)
poids d'expédition :	640 livres
nombre de lampes :	29
aspiration électrique :	23 ampères à 220 volts
circuit requis :	220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzeriez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Everglo 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W et [Everglo 59"/100W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable)]**. La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
III – Moyen	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
IV – Foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
V – Très foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 20 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



SPECIFICATIONS

124

LENGTH:	85.5L" X 36"W
WEIGHT:	585LBS
NUMBER OF LAMPS:	24
ELECTRICAL DRAW:	13AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 20AMP Breaker

124/1

LENGTH:	85.5L" X 36"W
WEIGHT:	600LBS
NUMBER OF LAMPS:	24, 1 facial lamp
ELECTRICAL DRAW:	16AMPS @ 220VOLTS*
CIRCUIT REQUIRED:	220VOLTS, with ground, 30AMP Breaker

*NOTE: Amperage will vary depending on voltage.

MELANIN - The brownish pigment produced by special cells in the base layer of the skin determines the individual's tan. As the skin is exposed to the ultraviolet light, the melanin is activated and combines with protein cells that rise to the skin's surface, thus producing a tan. The amount of melanin in your body determines how quickly and dark you tan. The more melanin produced and exposure time an individual has, the faster and deeper the individual will tan.

NOTE: The tan produced by the 124 is a deep, rich "COSMETIC" tan. However, regardless of how dark an individual may tan on this system, it will not provide adequate protections against overexposure to natural sunlight or UVB tanning systems.

SKIN TYPE II - This is the individual that usually burns easily and severely, tans minimally or lightly and peels
SKIN TYPE III - Often referred to as "AVERAGE" complexion. burns moderately and tans about average
SKIN TYPE IV - This individual burns minimally, tans easily and above average with each exposure
SKIN TYPE V - This individual rarely burns, tans easily and substantially

IMPORTANT NOTE:

Customers that wear contact lenses, should be made aware that the heat and ventilation wind may dry out their contacts and should be removed prior to the session.

Use only creams, oils or lotions (particularly suntan lotions) that are recommended by Heartland Tanning, Inc. Equally important - many facial makeups have oil bases and sun block should be removed prior to a session.

It is recommended that following a tanning session, a skin moisturizer be applied. This promotes a smoother, more even looking tan.

EXPOSURE SCHEDULE 124 and 124/1

DANGER - ULTRAVIOLET RADIATION. Follow instructions. Avoid overexposure. As with natural sunlight, overexposure can cause eye and skin injury and allergic reactions. Repeated exposure may cause premature aging of the skin and skin cancer. **Wear protective eyewear: failure to may result in severe burns or long-term injury to eyes.**

Medications or cosmetics may increase your sensitivity to the ultraviolet radiation. Consult physician before using sunlamp if you are using medications or have a history of skin problems or believe yourself especially sensitive to sunlight. If you do not tan in the sun, you are unlikely to tan from the use of this product.

This system is intended to be used only with Everglo 71"/100W lamps, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT (facial unit, where applicable)].

Questions on Sales or Service

Follow recommended exposure schedule for the skin type.

Heartland Tanning, Inc. • Lee's Summit, MO • 1-800-554-8268

RECOMMENDED EXPOSURE SCHEDULE					
Skin Type	Week1 1st - 3rd Treatments	Week2 4th - 6th Treatments	Week 3 7th - 10th Treatments	Week 4 11th - 15th Treatments	Weekly Subsequent Treatments
II - Fair	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
III - Average	4MINUTES	8MINUTES	12MINUTES	16MINUTES	20MINUTES
IV - Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
V - Dark Brown	4MINUTES	12MINUTES	16MINUTES	20MINUTES	20MINUTES
MAXIMUM EXPOSURE TIME IS 20 MINUTES This product is in conformity with performance standards for sunlamp products under CFR 21 Part 1040					

This unit utilized UVA lamps. **Replace only with Everglo 71"/100W lamps, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT (Facial unit, where applicable)].** The minimum exposure position is .5 inches (1.27 cm) from the lamps surface (preset by the mfg.). Read the instruction booklet before using this device. To use, lie down under canopy and pull down as far as adjustment will allow. **CAUTION: THE USE OF ANY OTHER POSITION MAY RESULT IN OVEREXPOSURE.**

Tanning can begin on a regular basis. An appearance of tanning normally appears after a few exposures and maximizes after four (4) weeks of exposure. **Use protective eyewear** whenever equipment is energized. Read the instruction booklet before using.

Caractéristiques

124

longueur :	85,5 pouces par 36 pouces
hauteur :	34 pouces (avec le couvercle fermé)
poids d'expédition :	585 livres
nombre de lampes :	24
aspiration électrique :	13 ampères à 220 volts
circuit requis :	220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

124/1

longueur :	85,5 pouces par 36 pouces
hauteur :	34 pouces (avec le couvercle fermé)
poids d'expédition :	600 livres
nombre de lampes :	25
aspiration électrique :	16 ampères à 220 volts
circuit requis :	220 volts, avec un disjoncteur différentiel, briseur de 30 ampères

DANGER – RAYONNEMENT ULTRAVIOLET. Suivez les instructions. Évitez la surexposition. Comme avec les rayons naturels du soleil, la surexposition peut causer dommage aux yeux et à la peau et des réactions allergiques. L'exposition répétée peut causer le vieillissement prématuré de la peau et du cancer de la peau. **Portez des lunettes protectrices; le non-respect de cette consigne peut entraîner de graves brûlures ou des lésions oculaires à long terme.**

Les médicaments ou les produits de beauté peuvent augmenter votre sensibilité au rayonnement ultraviolet. Consultez un médecin avant d'utiliser la lampe solaire si vous utilisez des médicaments ou avez une histoire des problèmes de peau ou croyez-vous particulièrement sensibles aux rayons du soleil. Si vous ne bronzes pas au soleil, il est peu probable que vous bronzerez avec l'utilisation de ce produit.

Questions au sujet des ventes ou de service : Heartland Tanning, Inc. • Lee's Summit, MO – 1-800-554-8268

Suivez le programme recommandé d'exposition pour le type de peau.

Cette appareil utilise des lampes de l'ultra-violet A. Remplacez seulement avec les lampes de marque **Everglo 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W et [Everglo 59"/100W, Philips HPA 400/30 S et Heraeus E-400 HPT (ampoule faciale de bronzage, là où applicable)]**. La position minimum d'exposition est à 0,5 pouces 1,27 cm) de la surface de la lampe (instituez par le fabricant). Lisez le livret d'instruction avant d'utiliser ce dispositif. Pour utiliser, couchez-vous sous l'écran et abaissez dans la mesure où le réglage laissera. **ATTENTION : L'UTILISATION DE N'IMPORTE QUELLE AUTRE POSITION PEUT AVOIR COMME CONSÉQUENCE LA SUREXPOSITION.**

Le bronzage peut commencer de façon régulière. Un aspect de bronzage normalement apparaît après quelques expositions et atteint son niveau maximal après quatre (4) semaines d'exposition. **Utilisez des lunettes protectrice à chaque fois que l'appareil est active.** Lisez le livret d'instructions avant l'utilisation.

Horaire d'exposition recommandé					
Type de peau	Semaine 1 1er – 3e Traitements	Semaine 2 4e – 6e Traitements	Semaine 3 7e – 10e Traitements	Semaine 4 11e – 15e Traitements	Bihebdomadaire Traitements subséquents
II – Claire	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
III – Moyen	4 MINUTES	8 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES
IV – Foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
V – Très foncé	4 MINUTES	12 MINUTES	16 MINUTES	20 MINUTES	20 MINUTES
LE TEMPS MAXIMUM D'EXPOSITION EST DE 20 MINUTES Ce produit est conforme aux normes de rendement pour des produits de lampe de soleil tel que stipule la partie 1040 du document CFR 21.					



WARNINGS AND CAUTIONS

Certain drugs - particularly those designed to produce photosensitivity - may cause individuals under the influence of this type drug to experience adverse effects and those people should avoid exposure to UV sources of all type. Doctors will advise persons taking these drugs of possible adverse effects.

It is recommended that only one (1) person at a time should use the tanning system, and advise using protective eyewear while using the tanning unit. Two (2) pair of protective eyewear are provided with each tanning bed sold.

WARNING

If you have been diagnosed by physician as being allergic to the sun or are currently taking photosensitive medications, consult you physician before using the tanning unit.

CAUTION

While there is no immediate clinical evidence regarding UVA exposure and its effects upon expectant mothers, it is strongly advised that expectant mothers be discouraged from using the tanning unit.

MANDATORY READING

ALWAYS FOLLOW INSTRUCTIONS FOR PROPER USAGE PRIOR TO USING ANY TANNING SYSTEM

REMEMBER

1. Follow the exposure schedule in accordance with you skin type. Failure to do so may result in overexposure.
2. Replacement lamps must comply with CFR 21 1040.20. When ordering lamps, include model number and serial number. See Lamp Guide on page 7 for the appropriate lamp replacements for your tanning bed.

Should you have any questions regarding the proper use of your tanning system, contact Heartland Tanning, Inc. at:

1-800-554-8268
8:00AM to 5:00PM (CST)

REPAIRS - SERVICE - REPLACEMENT PARTS AND LAMPS - EYE PROTECTION

If you are in need of any of the above mentioned products or services, you should contact the dealer/distributor through whom you purchased your unit. In the event that you are unable to do so, please call our Service Department for assistance at: 1-800-554-8268.

NOTE: All repairs and replacement components including, but not limited to, protective eyewear, lamps, timers and acrylic must be in compliance with CFR21 1040.20.

**NOTE: Electrical connection to power supply,
must be in compliance with NECA
regulations and performed by
a qualified electrician.**

**Warning:
Wear protective eyewear; failure to may result
in severe burns or long-term injury to eyes.**

CARE AND CLEANING OF YOUR TANNING BED

After each session is completed, spray acrylic with a specially formulated UVT (ultra-violet transmitting) acrylic cleaner. Wipe the acrylic with a clean cloth. The acrylic should never be wiped with a dry cloth because this will generate a slight static charge which will attract dust. A mild liquid detergent and water solution can be used temporarily in place of acrylic cleaner.

For maximum efficiency of your tanning bed, periodic cleaning of lamps is required. Refer to relamping instructions for acrylic removal.

CAUTION: Do not use excessive amounts of water, any abrasive cleaners, or any spray cleaner that carry label warnings regarding reactions to contact with skin!

DO NOT USE ALCOHOL

ELECTRICAL SAFETY: The tanning unit should be disconnected from the power supply before cleaning or any repairs are made! Avoid water or solution entering the lamp compartment.

America's best tan™

RELAMPING INSTRUCTIONS

1. Disconnect power from unit.
2. Remove acrylic strips and slide acrylic out of the unit.
3. Turn the bi-pin lamp 90 degrees and remove from lampholder.
4. Align the bi-pin lamp and slide the top and bottom into the lampholder turn 90 degrees.
5. Clean and replace acrylic. (Refer: care and cleaning instructions.)
6. Reconnect unit to power.

CAUTION

Replacement lamps must comply with CFR 21 1040.20

When ordering lamps, include model number and serial number.

LAMP GUIDE

***154, 154/3 - 12MINUTE**

Replace only with Cosmolux VHR 16180/160W lamps and Hi-Tan 10198/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)

***154, 154/3 - 15MINUTE**

Replace only with Cosmolux VHR 16180/160W lamps and Cosmolux VLR 16180/160W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)

***144, 144/3**

Replace only with Bellarium SR RA1-12/160W, Everglo 71"/100W lamps, Bellarium S SA1 71/100W or Durasun F71BP 100W, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)

134, 134/3

Replace only with Everglo 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)].

134 VLR, 134/3 VLR

Replace only with Cosmolux VLR 18810/100W lamps and Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)

134C

Replace only with Cosmostar Longlife 12503/100W lamps

128, 128/1

Replace only with Everglo 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)].


124, 124/1

Replace only with Everglo 71"/100W, Durasun F71BP 100W, Bellarium S SA1 71/100W and [Everglo 59"/100W lamps, Philips HPA 400/30 S lamps and Heraeus E-400 HPT lamps (Facial unit, where applicable)]

* Please note - when removing canopy acrylic from these units - requirement is 2 people, 1 person at each end of bed for ease of removal and installation.

REPLACING 154/3, 144/3 AND 134/3 FACIAL LAMPS

1. DISCONNECT POWER FROM UNIT.
2. REMOVE (2) PHILLIPS PAN HEAD SCREWS (AT FRONT EDGE OF THE ACRYLIC) USING A #2 PHILLIPS SCREW DRIVER OR SCREW GUN.
3. PULL FRONT EDGE OF ACRYLIC/RAIL DOWN FROM CANOPY ALLOWING THE ACRYLIC TO HINGE DOWN FROM THE BACK SIDE.
4. REMOVE ACRYLIC FROM HINGE RAIL. EXPOSING FACIAL ASSEMBLY.
5. WHILE HOLDING FACIAL GLASS CASSETTE, REMOVE (4) RETAINING SCREWS USING A #2 PHILLIPS.



6. REMOVE FACIAL GLASS CASSETTE FROM FACIAL HOUSING EXPOSING 400 WATT FACIAL LAMP.
7. GRASP LAMP AT ONE END PRESSING TOWARDS THE OPPOSITE END TO RELEASE FROM LAMP BRACKET.
8. TO REPLACE 400 WATT FACIAL LAMP REVERSE PROCEDURES ABOVE. FOR MULTIPLE FACIALS, DUPLICATE STEPS ABOVE FOR EACH SINGULAR LAMP BEING REPLACED.


NOTE: ONLY GRASP 400 WATT FACIAL LAMP FROM EITHER END; ALWAYS USE ALCOHOL TOWEL PROVIDED WITH LAMP TO WIPE OFF LAMP AFTER INSTALLATION.

CAUTION: DO NOT CHECK FACIAL LAMP OPERATION WITH FACIAL GLASS CASSETTE REMOVED.

***ALWAYS WEAR UV PROTECTIVE EYEWEAR WHEN REPLACING LAMPS AND CHECKING OPERATION.**

REPLACING 128/1 AND 124/1 FACIAL LAMP

1. DISCONNECT POWER FROM UNIT.
2. REMOVE (2) PHILLIPS PAN HEAD SCREWS (AT FRONT EDGE OF THE ACRYLIC) USING A #2 PHILLIPS.
3. PULL FRONT EDGE OF ACRYLIC/RAIL DOWN FROM CANOPY ALLOWING THE ACRYLIC TO HINGE DOWN FROM THE BACK SIDE.
4. REMOVE ACRYLIC FROM HINGE RAIL. EXPOSING FACIAL ASSEMBLY.
5. WHILE HOLDING FACIAL GLASS CASSETTE, REMOVE (4) RETAINING SCREWS USING A #2 PHILLIPS.



6. REMOVE FACIAL GLASS CASSETTE FROM FACIAL HOUSING EXPOSING 400 WATT FACIAL LAMP.
7. GRASP LAMP AT ONE END PRESSING TOWARDS THE OPPOSITE END TO RELEASE FROM LAMP BRACKET.
8. TO REPLACE 400 WATT FACIAL LAMP REVERSE PROCEDURES ABOVE.

NOTE: ONLY GRASP 400 WATT FACIAL LAMP FROM EITHER END; ALWAYS USE ALCOHOL TOWEL PROVIDED WITH LAMP TO WIPE OFF LAMP AFTER INSTALLATION.

CAUTION: DO NOT CHECK FACIAL LAMP OPERATION WITH FACIAL GLASS CASSETTE REMOVED.

***ALWAYS WEAR UV PROTECTIVE EYEWEAR WHEN REPLACING LAMPS AND CHECKING OPERATION.**

USE AND GUIDE TO TIMER SYSTEM

(C) COPYRIGHT 1999 by Salon Systems, Inc.

The information in this manual is believed to be correct. However, Salon Systems, Inc. assumes no responsibility for any errors herein.

This information is subject to change without notice, and should not be construed as a commitment by Salon Systems, Inc.

A factory 3 second delay between all functions is standard on all Ovation™ beds.

TIMER WARRANTY

This product is warranted against defective materials and workmanship for a period of one year from date of purchase. In the event the product fails to perform, it may be returned; Shipping Paid, to the factory to be serviced or replaced at the factory's discretion. Salon System, Inc. will pay to ship the repaired or replaced product by the shipping means of our choosing. Returns will not be accepted without a Return Authorization Number assigned by the factory. It is a Condition of Sale that the user of Salon Systems, Inc.'s products assumes all risk and responsibility of use and indemnifies Salon Systems, Inc. against all damages. Salon Systems Inc. is not liable for loss of profits, loss savings, special, incidental, consequential, indirect or other similar damages arising from breach of warranty, breach of contract, negligence, or other legal action even if Salon Systems, Inc. or its agent has been advised of the possibility of such damages, or for any claim brought against you by another party. This warranty allocates risks of product failure between the Purchaser and Salon Systems, Inc. Salon Systems, Inc.'s hardware pricing reflects this allocation of risk and the limitations of liability contained in this warranty. It is a violation of the stated warranty to cut or modify the provided modular cables supplied with the T-Max Series Timers. Connection the T-Max Series to third party timers not approved by Salon Systems, Inc. also violates the stated warranty. Contact your dealer or Salon Systems, Inc. if you are not sure if the timer that you are connection is an approved timer.

T-Max/004 OEM Installation and User's Guide

OVERVIEW

Congratulations on your purchase of Salon Systems, Inc.'s T-Max Series of tanning bed timers. The T-Max Series is designed for complete automation and control of your tanning equipment.

A Heartland Timer is an OEM board that can be installed in a tanning bed or tanning booth. Each Heartland Timer can individually control a tanning bed, can be connected back-to-back with a T-Max 1A or T-Max 3A for remote front desk control or be connected with many Heartland Timers and a T-Max Manager or Manager/Plus to control many beds from a remote location. Operation is accomplished via front panel controls. This manual should be used by the licensed electrician installing your T-Max timing system. Check for compliance with local building codes.

CONFIGURATION

Setting Parameters

Note: If you are using a T-Max Manager or T-Max Manager/Plus and multiple Heartland Timers, remove power from the T-Max Manager or T-Max Manager/Plus and keep the power removed until all parameter changes are complete.

1. Press and hold the Start/Stop and the Up buttons simultaneously on the Heartland Timer. As soon as you see a ".1" on the display release the buttons. This should take about 5-6 seconds. This is an indication that you are in the parameter mode. The numbers currently displayed represents the parameter number that you can observe or change.
2. Press the Up and Down buttons until the parameter number that you want to observe or change is displayed.

- 3 Press the Start/Stop button. The current value for that parameter will be displayed and flashing.

The Heartland Timer will show a number with a period illuminated in the lower center of the display. The number shown is the current value for that parameter.

For Lamp, Session Counts, etc. the value displayed can be as high as 9999. To display this value, the Heartland Timer will flash tow numbers-three times, then two numbers-three times, pause, two numbers-three times, two numbers-three times, pause, etc. For example, if you are checking lamp hours (Parameter 6) and the display flashes the numbers 53 three times, then 14 three times, pauses then repeats, then the total lamp hours stored in that Heartland Timer is 5314.

4. Press the Up and Down buttons to change the parameter to the desired value.
If you want to clear the value for that parameter, press the Up and Down buttons at the same time until the display shows 0.0.
5. Press the Start/Stop button.
The display will show the parameter number you just change and a solid period in the lower center of the display. You may now change another parameter by pressing the Up and Down buttons until the parameter that you want to change is displayed. Repeat Steps 2-4 for each parameter you want to change.
6. To exit the Parameter mode and make the Heartland Timer available for the next session, press and hold the both Up and Down buttons until the display shows a 0 with no periods displayed.

Setting The Address

Note: If you are using the Heartland Timer as an independent timer, you don't need to set the address on the Heartland Timer.

1. Press and hold the Start/Stop buttons simultaneously on the Heartland Timer until a .1 appears on the display. Release the buttons. This should take about 5-6 seconds.
2. Press and release the Start/Stop button. A number will appear on the display and be flashing. A period will be illuminated in the center of the display. Pressing and holding the Up button will cause the display to count up. Once the count reaches 100, the center period will flash rapidly. This is an indication that you are over 99. For example, if the display shows a 0.2 with the period flashing, this is address 102. The highest the display will count up is 254.
3. Press the Up and Down buttons until the desired address is displayed. When setting the address, remember 3 rules:
 A) Set each Heartland Timer to a unique address. B) Do not set any address to 0.
 C) Do not set any address over 100.
4. Press the Start/Stop button. The ".1" will appear on the display. The 1 will not be flashing.
5. To exit, press and hold both Up and Down buttons until the display shows a 0 with no periods displayed.

Table 1 - Parameter numbers for observing and changing parameters.

Param.#	Description	Max #	Default	Notes
Salon Level				
1	Address	128	1	Set this number to the room number you want the timer to be
2	Beep Mode	1	0	Used for High Power beds. 0=Alarm Only, 1=Alarm and Flip
3	Delay Time	10	3	Delay in minutes stored in the Heartland Timer
5	Session	65535	0	Total Session counts for Heartland Timer Counts
6	Lamp Hours	65535	0	Bulb hours for each bed
7	Bed Hours	65535	0	How many hours a bed is on
8	Manual Session Counts	65535	0	Counts the # of sessions the Heartland Timer Session has run while in Stand Alone Mode
9	Clean Room	1	1	0 = Clean Room Disabled. 1 = Enabled
10	Manual Lockout*	1	0	0 = Stand Alone Enabled. 1 = Disabled
13	Cool Down Mode	10	3	0 = Disabled, 1-10 = Enabled. Time delay in minutes allowing bed to cool. The fans will remain running while the Heartland Timer is in cool down mode.
14	5 Min. Beep	1	0	0 = Disabled, 1 = Enabled. Heartland Timer will beep for 10 seconds every 5 minutes
15	Fixed Session	65535	0	Counts number of sessions ran through the TMax® 3A. This value cannot be changed at all. Used as point of reference.
16	Pulse Mode	1	0	0 = Disabled, 1 = Enabled. When session starts, the relay on the T-Max® 1A will close for 1-2 seconds then open.
17	Clean Clear	1	0	0 = Press and hold the Set button for 3-4 seconds to clear the clean room. 1 = Press and release the Set button to instantly clear the clean room.
18	Redisplay	2	0	0 = After a session ends and the clean room is cleared, the Heartland Timer will show a 0. 1 = After session ends and the clean room is cleared, the Heartland Timer will show the last session time entered. 2 = After the session ends and the clean room is cleared, the max. time will show on the Heartland Timer.
19*	Third Part Interface	1	0	When set to a 1, voltage must be applied by an outside source to the TPI input on the back of the Heartland Timer. Used if the timer is being controlled by either a FST® or Database® Series Timer. See Section for JPI settings

Setting Delay Time

If the Heartland Timer is being controlled by a T-Max 1A, T-Max 3A, T-Max Manager or T-Max Manager/Plus, the delay does not need to be set on the Heartland Timer. The delay is controlled by the controlling device.

1. Press and hold the Start/Stop and Up buttons simultaneously the Heartland Timer until a ".1" appears on the display. Release the buttons. This should take about 5-6 seconds.
2. Press the Up and Down button until a ".3" is displayed.
3. Press and release the Start/Stop button. A number will appear on the display and be flashing. A period will be illuminated in the center of the display. This is the current delay time.
4. Press the Up and Down button until the desired delay time is displayed. The highest delay time that can be set on the Heartland Timer is 10 minutes. If you want no delay time, set the display to 0. If you set the delay time to 0, the session time will start immediately after the Start/Stop button is pressed.
5. Press the Start/Stop button. The ".3" will appear on the display. The 3 will not be flashing.
6. To exit, press and hold both the Up and Down buttons until the display shows a "0" with no periods displayed.

IN-ROOM SINGLE BED CONTROL

Starting A Session

1. Press the Up and Down button on the Heartland Timer until the desired session time is displayed. If the display shows a 0, and you want to count down from the maximum time, press the down button.
2. Press and release the Start/Stop button to start the session. If a delay other than 0 is entered, the delay will count down. A period on the lower right corner of the display will flash rapidly. When the session starts, the period will flash at a once per second rate. If the delay is set to 0, the session will start immediately.

Pausing A Session

To pause the session press the Start/Stop button. The flashing period on the lower right corner of the display will stop flashing and stay illuminated. To restart, press the Start/Stop button on the Heartland Timer. The period on the lower right corner of the display will resume flashing.

NOTE: The session time will continue to count down. The display will continue to update and reflect the remaining session time.

Canceling A Session

To cancel a session, press the Start/Stop button to pause the session then press the Up button. The display will show a solitary 0.

REMOTE SINGLE BED CONTROL

Remote Single Bed Control is the ability to control a single tanning bed from a remote location. T-Max 3A at the remote location is required for this configuration.

Wiring

Wire the Heartland Timer to the tanning bed. Apply power to the T-Max 3A as described in their respective User's Guides.

Run the provided modular cable from the tanning room to the remote T-Max 3A or T-Max 1A. Connect the modular cable to one of the RJ-22 ports on the Heartland Timer and T-Max 1A or T-Max 3A (see RJ-22 ports for T-Max Series timers on page 16, figure B).

Configuration

Set the address on the Heartland Timer in the tanning room to 1. Set the address on the T-Max 3A to 0.0. For setting the delay refer to the T-Max 3A user's guide.

Note: When setting the address on the Heartland Timer in the tanning room, the power to the front desk T-Max 1A or 3A must be off.

Session Control

Starting a session

1. Press the Up and Down button on the T-Max 3A or the Set button on the T-Max 1A at the front desk until the session time is displayed. Time cannot be set from the Heartland Timer in the room.
2. Press the Start/Stop button on the front desk T-Max 1A or T-Max 3A to start the session.

If a delay other than 0 is set, the delay will count down. A period on the lower right corner of the display will flash rapidly.

When the session starts, the period will flash at once per second rate. If a 0 delay is entered, the session will start immediately.

Pause during the Session

To pause the session press the Start/Stop button on the Heartland Timer in the tanning room. The flashing period on the lower right corner of the display will stop flashing and stay illuminated. To restart the session, press the Start/Stop button on the Heartland Timer in the tanning room. The period will continue flashing.

Note: The session time will continue to count down. The display will continue to update and reflect the remaining session time.

Canceling a session

To cancel a session, press both the Start/Stop and Up button on the T-Max 3A at the front desk simultaneously. If you are using a T-Max 1A, press the Start/Stop and the Set buttons simultaneously. The session cannot be canceled from the Heartland Timer.

USING THE HEARTLAND TIMER WITH A T-MAX MANAGER OR T-MAX MANAGER/PLUS/PRO

If you are using Heartland Timers with a T-Max Manager or T-Max Manager/Plus, follow these instructions for proper operation:

1. Set the address on each Heartland Timer.

Note: If this is a first time installation, go through the quick installation procedure in Section 2 of the T-Max Manager or T-Max Manager/Plus user's guides. This will automatically set the address on the Heartland Timers and you will not need to set the addresses manually as described in the following steps. If you need to set the address on the Heartland Timer manually, be sure to set each Heartland Timer to a different address. No Heartland Timer should be set to address 00.

2. Connect each Heartland Timer together using a modular cable that conforms to the pinouts shown on Figure B. Connect T-Max Manager or T-Max Manager/Plus to the closest Heartland Timer in the line (refer to Figure C).

Note: Delay is controlled by the T-Max Manager, the T-Max Manager/Plus or the software you are using if you are using a computer. It is not necessary to set the delay on the Heartland Timer. Refer to the T-Max Manager or T-Max Manager/Plus User's Guide for operation.

OTHER FEATURES

Clean Room

Once a session time has elapsed, the display will show two solid periods only. This is an indication that the room needs to be cleaned. To clear the clean room indication, press and hold the Up button on the Heartland Timer in the tanning room until the two period disappear and a "0" appears. To disable the clean room feature, set parameter 9 to a 0.

Lamp Hours

To check and change Lamp Hours (or any other parameter).

TPI (Third Party Input) Mode

If you are using a FST or Database Series timers, you will need to place the Heartland Timer in the TPI mode.

Connecting the TPI Input

1. Set Parameter 19 to a 1.
2. Connect the two actuator wires from the FST or Database timer to the TPI input in the back of the Heartland timer. When a session is started the FST timer will place 5v on these two wires. If you are using a database Series timer, 24 volts will be applied.

Connecting the TPI output

FST:

1. There are three wires coming from the FST series timer. Two are the actuator wires connected to the signal input. Connect the third wire to one of the switch terminals. Make sure J6 and J7 are on and J4 and J5 are off.
2. Run a jumper from the black actuator wire connected to the other switch screw terminal.

Database:

There are four wires coming from the database series timer. Two are the actuator wires connected to the signal input. Connect the two other wires to the TPI relay output terminal J1. Make sure J6, J4 and J5 are off and J7 is on. Contact closure

If your external timer is simply a relay contact closure, make sure J4, J6, and J5 are on and J7 is off.

Important: J4, J5, and J7 should never be on at the same time!!!

Operation

When a session is started, voltage will be applied to the TPI input. The display on the Heartland Timer will show the maximum time and count down. When the session ends, the voltage will be removed from the TPI input and the bed will turn off. Any remaining session time showing on the Heartland Timer will be eclipsed.

Note: The Heartland timer can not be used as a stand alone time in the TPI mode.

If the FST or Database Series timers are in delay the Heartland Timer will show a 0. However, pressing the Start/Stop button on the Heartland Timer will eclipse the delay time and start the session. Pressing the Start/Stop button on the Heartland timer will also clear the clean room indication on the FST and Database timers.

Cool down mode


Cool down mode is the time the bed needs to cool down after a session has ended. The Factory default setting is 3 minutes.

1. Connect the wires that control the fans to the headers on the back of the Heartland timer.
2. Set parameter 13 to the desired cool down time.
After a session has ended the display will show a single period in the middle of the display. The period will remain until the cool down time has elapsed. The display will then show a 0.

Note: If both cool down time and clean room are enabled, the clean room will be displayed. If the clean room indication is cleared before the cool down time has expired, the cool down indication will be displayed. If the cool down time has elapsed before the clean room indication has been cleared, the clean room indication will remain until it is cleared.

Figure A - Front View Of The Heartland Timer


Display Board Front View



Note: D6 - Run and communications indication lights. Will flash at a once per second rate when operating a stand alone mode. When flashing rapidly the communications are active (either with a T-Max® Manager or Master T-Max® 3A). Will stay on solid if timer is in TPI mode.

D5 - Power indication.

Figure B - Power Board Location



**T-Max Remote
or T-Max Manager/
Plus/Pro**





FIGURE C - Connecting the Heartland Timer to a T-Max® Series



It does not matter in which order the rooms are connected. The only requirement is that there is a continuous connection from the T-Max® Manager through each room in the T-Max® Series daisy-chain.

154, 154/3, 144/3 and 144 Bed Assembly and Wiring Diagrams

154, 154/3, 144 and 144/3


ASSEMBLY INSTRUCTIONS

TOOLS YOU WILL NEED:

- A. 1/2" RATCHET DRIVE
- B. 9/16" RATCHET DRIVE
- C. 7/16" RATCHET DRIVE
- D. TWO (2) OR MORE PEOPLE

STEP 1: FIND THE TWO LEG ASSEMBLIES. POSITION THE BASE AND THE LEGS OF THE 154 INTO THEIR FINAL RESTING PLACE.


STEP 2: ATTACH THE LEGS TO THE BASE USING (4) 1/4 - 20 X 7/8 BOLTS AS SHOWN BELOW.




STEP 3: INSTALL BALLAST TRAYS. THE 160 WATT TRAY INSTALLS ON THE LEFT SIDE OF THE BASE AND THE 100 WATT ON THE RIGHT.

STEP 4: FIND BASE FAN WIRES IN 160 WATT TRAY ON LEFT HAND SIDE, ATTACH TO FAN WIRES ON REAR OF BASE.


STEP 5: INSTALL CANOPY. TO DO THIS, POSITION CANOPY ON TABS ON THE END OF THE LEG ASSEMBLY. THE CANOPY **WILL** STAY IN PLACE AFTER IT IS HINGED.



STEP 6: ROUTE CORDS 3 AND 4 FROM THE 160W BALLAST TRAY THROUGH HOLE IN BACK OF BASE AS SHOWN BELOW.



STEP 7: INSTALL 8 - 5/16 x 1 1/4 HEX BOLTS IN TOP OF CANOPY. TIGHTEN ALL THE WAY DOWN.




STEP 8: CONNECT CORDS 3 AND 4 TO BACK OF CANOPY.

STEP 9: INSTALL BENCH - POSITION STUDS ON BOTTOM OF BENCH WITH HOLES IN THE BASE. ATTACH 4-3/8 FLANGE NUTS TO STUDS IN BENCH.

NOTE: POSITION BENCH SO THAT DISPLAY TIMER IS IN BACK OF THE UNIT. PLUG TIMER INTO THE 100 WATT BALLAST TRAY (SEE TIMER SECTION FOR DETAILS).

STEP 10: ATTACH CORD 1 AND 2 TO BOTTOM SIDE OF BENCH.




STEP 11: ATTACH FRONT FACADE

IF YOU HAVE ANY QUESTIONS, PLEASE CALL: 1-800-554-8268

154 AND 144 SERIES


HARNESS CORD #1 / RECEPTACLE #1



PIN#	COLOR	PLUG LOCATION	RECEPTACLE LOCATION
1	Blue	Lamp 1 head end	Ballast 1-1
2	Yellow	Lamp 2 head end	Ballast 1-2
3	Orange	Lamp 3 head end	Ballast 1-3
4	Purple	Lamp 4 head end	Ballast 1-4
5	Grey	Lamp 5 head end	Ballast 1-5
6	Pink	Lamp 6 head end	Ballast 1-6
7	Tan	Lamp 7 head end	Ballast 1-7
8	Light Blue	Lamp 8 head end	Ballast 1-8
9	White/Orange	Lamp 9 head end	Ballast 1-9
10	White/Blue	Lamp 10 head end	Ballast 1-10
11	Empty		
12	Empty		
13	Empty		
14	Empty		
15	Empty		
16	White/Red	Fan Circuit	Contactor-Fan
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Contactor-Fan
23	Empty		
24	Empty		
25	Empty		
26	Empty		
27	Empty		
28	Blue	Lamp 1 foot end	Capacitor 1-1
29	Yellow	Lamp 2 foot end	Capacitor 1-2
30	Orange	Lamp 3 foot end	Capacitor 1-3
31	Purple	Lamp 4 foot end	Capacitor 1-4
32	Grey	Lamp 5 foot end	Capacitor 1-5
33	Pink	Lamp 6 foot end	Capacitor 1-6
34	Tan	Lamp 7 foot end	Capacitor 1-7
35	Light Blue	Lamp 8 foot end	Capacitor 1-8
36	White/Orange	Lamp 9 foot end	Capacitor 1-9
37	White/Blue	Lamp 10 foot end	Capacitor 1-10

Lamp orientation is from FRONT of unit to BACK of unit (#1 through #20)

HARNESS CORD #2 / RECEPTACLE #2




PIN#	COLOR	PLUG LOCATION	RECEPTACLE LOCATION
1	Blue	Lamp 11 head end	Ballast 2-1
2	Yellow	Lamp 12 head end	Ballast 2-2
3	Orange	Lamp 13 head end	Ballast 2-3
4	Purple	Lamp 14 head end	Ballast 2-4
5	Grey	Lamp 15 head end	Ballast 2-5
6	Pink	Lamp 16 head end	Ballast 2-6
7	Tan	Lamp 17 head end	Ballast 2-7
8	Light Blue	Lamp 18 head end	Ballast 2-8
9	White/Orange	Lamp 19 head end	Ballast 2-9
10	White/Blue	Lamp 20 head end	Ballast 2-10
11	Empty		
12	Empty		
13	Empty		
14	Empty		
15	Empty		
16	White/Red	Fan Circuit	Contactor-Fan
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Contactor-Fan
23	Empty		
24	Empty		
25	Empty		
26	Empty		
27	Empty		
28	Blue	Lamp 11 foot end	Capacitor 2-1
29	Yellow	Lamp 12 foot end	Capacitor 2-2
30	Orange	Lamp 13 foot end	Capacitor 2-3
31	Purple	Lamp 14 foot end	Capacitor 2-4
32	Grey	Lamp 15 foot end	Capacitor 2-5
33	Pink	Lamp 16 foot end	Capacitor 2-6
34	Tan	Lamp 17 foot end	Capacitor 2-7
35	Light Blue	Lamp 18 foot end	Capacitor 2-8
36	White/Orange	Lamp 19 foot end	Capacitor 2-9
37	White/Blue	Lamp 20 foot end	Capacitor 2-20

Lamp orientation is from FRONT of unit to BACK of unit (#1 through #20)

154 AND 144 SERIES


HARNESS CORD #3 / RECEPTACLE #3



PIN#	COLOR	PLUG LOCATION	RECEPTACLE LOCATION
1	Blue	Lamp 1 head end	Ballast 3-1
2	Yellow	Lamp 2 head end	Ballast 3-2
3	Orange	Lamp 3 head end	Ballast 3-3
4	Purple	Lamp 4 head end	Ballast 3-4
5	Grey	Lamp 5 head end	Ballast 3-5
6	Pink	Lamp 6 head end	Ballast 3-6
7	Tan	Lamp 7 head end	Ballast 3-7
8	Light Blue	Lamp 8 head end	Ballast 3-8
9	White/Orange	Lamp 9 head end	Ballast 3-9
10	White/Blue	Lamp 10 head end	Ballast 3-10
11	White/Green	Lamp 11 head end	Ballast 3-11
12	Black/Red	Lamp 12 head end	Ballast 3-12
13	Red/Black*	Facial Ignitor #1	Facial Ballast #1
14	Red	Fan Circuit	Contactor-Fan
15	Red/Yellow*	Facial Ignitor #2	Facial Ballast #2
16	White/Red	Fan Circuit	Contactor-Fan
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Contactor-Fan
23	Black/Yellow*	Facial Ignitor #2	Facial Term. Strip
24	White/Black	Fan Circuit	Contactor-Fan
25	Black/Red*	Facial Ignitor #1	Facial Term. Strip
26	Blue	Lamp 1 foot end	Capacitor 3-1
27	Yellow	Lamp 2 foot end	Capacitor 3-2
28	Orange	Lamp 3 foot end	Capacitor 3-3
29	Purple	Lamp 4 foot end	Capacitor 3-4
30	Grey	Lamp 5 foot end	Capacitor 3-5
31	Pink	Lamp 6 foot end	Capacitor 3-6
32	Tan	Lamp 7 foot end	Capacitor 3-7
33	Light Blue	Lamp 8 foot end	Capacitor 3-8
34	White/Orange	Lamp 9 foot end	Capacitor 3-9
35	White/Blue	Lamp 10 foot end	Capacitor 3-10
36	White/Green	Lamp 11 foot end	Capacitor 3-11
37	Black/Red	Lamp 12 foot end	Capacitor 3-12

*If unit is equipped with 3 Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #24)

HARNESS CORD #4 / RECEPTACLE #4




PIN#	COLOR	PLUG LOCATION	RECEPTACLE LOCATION
1	Blue	Lamp 13 head end	Ballast 4-1
2	Yellow	Lamp 14 head end	Ballast 4-2
3	Orange	Lamp 15 head end	Ballast 4-3
4	Purple	Lamp 16 head end	Ballast 4-4
5	Grey	Lamp 17 head end	Ballast 4-5
6	Pink	Lamp 18 head end	Ballast 4-6
7	Tan	Lamp 19 head end	Ballast 4-7
8	Light Blue	Lamp 20 head end	Ballast 4-8
9	White/Orange	Lamp 21 head end	Ballast 4-9
10	White/Blue	Lamp 22 head end	Ballast 4-10
11	White/Green	Lamp 23 head end	Ballast 4-11
12	Black/Red	Lamp 24 head end	Ballast 4-12
13	Empty		
14	Red	Fan Circuit	Contactor-Fan
15	Empty		
16	White/Red	Fan Circuit	Contactor-Fan
17	Red/Green*	Facial Ignitor #3	Facial Ballast #3
18	Red/White	Facial Fan Switch	Contactor-Facial-Control
19	Green	Ground	Ground
20	Black/White	Facial Fan Switch	Timer Board
21	Black/Green*	Facial Ignitor #3	Facial Term. Strip
22	Black	Fan Circuit	Contactor-Fan
23	Empty		
24	White/Black	Fan Circuit	Contactor-Fan
25	Empty		
26	Blue	Lamp 13 foot end	Capacitor 4-1
27	Yellow	Lamp 14 foot end	Capacitor 4-2
28	Orange	Lamp 15 foot end	Capacitor 4-3
29	Purple	Lamp 16 foot end	Capacitor 4-4
30	Grey	Lamp 17 foot end	Capacitor 4-5
31	Pink	Lamp 18 foot end	Capacitor 4-6
32	Tan	Lamp 19 foot end	Capacitor 4-7
33	Light Blue	Lamp 20 foot end	Capacitor 4-8
34	White/Orange	Lamp 21 foot end	Capacitor 4-9
35	White/Blue	Lamp 22 foot end	Capacitor 4-10
36	White/Green	Lamp 23 foot end	Capacitor 4-11
37	Black/Red	Lamp 24 foot end	Capacitor 4-12

*If unit is equipped with 3 Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #24)

154 AND 144 SERIES

HARNESS CORD #5 / RECEPTACLE #5




PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Red/Black	Contactor-Lamps	Lamp-Term. Strip
2	Red/Black	Contactor-Lamps	Lamp-Term. Strip
3	Red/Black	Contactor-Lamps	Lamp-Term. Strip
4	Red/Black	Contactor-Lamps	Lamp-Term. Strip
5	Empty		
6	Empty		
7	Empty		
8	Empty		
9	Empty		
10	Red*	Contactor-Fan	Facial Contactor
11	Red*	Contactor-Fan	Facial Contactor
12	Empty		
13	Empty		
14	Red	Contactor-Fan	Fan.-Term. Strip
15	Red	Contactor-Fan	Fan.-Term. Strip
16	Empty		
17	Empty		
18	Green	Ground	Ground
19	Green	Ground	Ground
20	Black/White*	Timer Board	Black/White from #4
21	Empty		
22	Empty		
23	Black	Contactor-Fan	Fan.-Term. Strip
24	Black	Contactor-Fan	Fan.-Term. Strip
25	Empty		
26	Empty		
27	Black	Contactor-Fans	Facial Contactor
28	Black	Contactor-Fans	Facial Contactor
29	Empty		
30	Empty		
31	Empty		
32	Empty		
33	Empty		
34	Black/Red	Contactor-Lamps	Lamp-Term. Strip
35	Black/Red	Contactor-Lamps	Lamp-Term. Strip
36	Black/Red	Contactor-Lamps	Lamp-Term. Strip
37	Black/Red	Contactor-Lamps	Lamp-Term. Strip

*If unit is equipped with 3 Facial Cassettes

Lamp orientation is from FRONT of unit to BACK of unit (#1 through #24)

154 & 144 SERIES WIRING DIAGRAM BALLAST BOX



[] = CAPACITOR

[] = BALLAST


HOUR METER

Body C: MECHANICAL POSITIONING
144, 144/3, 154 & 154/3 Ballast Tray
100 Watt Tray (rightside tray)


FRONT OF BALLAST

154 & 144 SERIES WIRING DIAGRAM BALLAST BOX


REAR OF BALLAST TRAY



154 & 144 SERIES WIRING DIAGRAM BALLAST BOX




154 & 144 SERIES WIRING DIAGRAM FACIAL TRAY




154 & 144 SERIES WIRING DIAGRAM BALLAST BOX

BACK OF BALLAST TRAY



154 & 144 SERIES ELECTRICAL OVERVIEW




**134, 134/3, 134 VLR, 134/3 VLR, 134C
128 and 128/1
Bed Assembly
and Wiring Diagrams**

134, 134/3, 134 VLR, 134/3 VLR 134C, 128 and 128/1 ASSEMBLY INSTRUCTIONS

TOOLS YOU WILL NEED:

- A. 9/16" SOCKET
- B. 7/16" SOCKET
- C. 1/4" ALLEN WRENCH (PROVIDED)
- D. 5/32" ALLEN WRENCH (PROVIDED)
- E. 13mm SOCKET OR ADJUSTABLE CRESCENT WRENCH
- F. TWO (2) OR MORE PEOPLE

STEP 1: POSITION THE BENCH UPSIDE DOWN. DETERMINE LEFT AND RIGHT LEGS BY POSITIONING THE SHOULDER BOLTS ON THE LEGS TO THE INSIDE AND FRONT OF THE UNIT. USING THE 1/4" - 20X 7/8 BOLTS AND 1/4" WASHERS PROVIDED AND BOLT THE LEGS TO THE BENCH. (USING THE 7/16 SOCKET WRENCH).




STEP 2: TURN THE UNIT RIGHT SIDE UP, PLACE THE CANOPY ON THE TOP OF THE BENCH ALIGNING THE HINGE PLATES, BOLT THE HINGE PLATES TOGETHER (USING THE 1/2" X 1 1/4" SHOULDER BOLT, 3/8" NUT, 9/16" SOCKET AND THE 1/4" ALLEN WRENCH).

STEP 3: ALIGN HOLES IN BRAKE WITH HOLES IN THE HINGE BRACKET, BOLT TOGETHER WITH 10-24 X 1" SOCKET HEAD AND 5/32" ALLEN WRENCH.

STEP 4: USING 5/32" ALLEN WRENCH PROVIDED TIGHTEN THE BRAKE ADJUSTMENT SCREW UNTIL SNUG. **(DO NOT OVERTIGHTEN)**

STEP 5: REMOVE NUT FROM EACH END OF THE SHOCK. ATTACH PAINTED END OF SHOCK TO CANOPY, ATTACH SILVER END TO BENCH. TIGHTEN NUTS ON EACH END OF SHOCK. THE SILVER PART OF SHOCK ATTACHES TO CENTER POSITION ON BENCH.
(FOR PROPER CANOPY ADJUSTMENT, SEE NOTE BELOW).

NOTE: PROPER CANOPY ADJUSTMENT - IF CANOPY RAISES ON IT'S OWN, MOVE SHOCK ADJUSTMENT ON BENCH TO REAR POSITON. IF CANOPY FALLS TO QUICKLY, MOVE SHOCK ADJUSTMENT ON BENCH TO FORWARD POSITION.



STEP 6: REMOVE COVER ON BALLAST TRAY. LOCATE BLACK TIMER WIRE FROM BOTTOM OF BENCH. PLUG IN BLACK TIMER WIRE TO TIMER BOARD INSIDE BALLAST TRAY. REINSTALL COVER ON BALLAST TRAY. (SEE TIMER SECTION FOR DETAILS).

STEP 7: PLACE THE BALLAST BOX BETWEEN THE LEGS OF THE UNIT. RUN CORDS 1 AND 2 FROM THE BENCH TO THE BALLAST BOX, RUN CORDS 3 AND 4 FROM THE CANOPY TO THE BALLAST BOX. PLACE THE FRONT FACADE ONTO THE FRONT OF THE UNIT.

WARNING: TO INSURE PROPER INSTALLATION OF CORDS, TIGHTEN CORDS UNTIL THEY LOCK.


NOTE: WEAR PROTECTIVE EYEWEAR: FAILURE TO DO SO MAY RESULT IN SEVERE BURNS OR LONG-TERM INJURY TO EYES.

NOTE: ELECTRICAL CONNECTION TO POWER SUPPLY MUST BE IN COMPLIANCE WITH NECA REGULATIONS AND PERFORMED BY A QUALIFIED ELECTRICIAN.

IF YOU HAVE ANY QUESTIONS, PLEASE CALL: 1-800-554-8268

134 SERIES AND 128 SERIES


HARNESS CORD #1 / RECEPTACLE #1



PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 1 head end	Ballast 1-1
2	Yellow	Lamp 2 head end	Ballast 1-2
3	Orange	Lamp 3 head end	Ballast 1-3
4	Purple	Lamp 4 head end	Ballast 1-4
5	Grey	Lamp 5 head end	Ballast 1-5
6	Pink	Lamp 6 head end	Ballast 1-6
7	Tan	Lamp 7 head end	Ballast 1-7
8	Light Blue	Lamp 8 head end	Ballast 1-8
9	Empty		
10	Empty		
11	Empty		
12	Empty		
13	Empty		
14	Red	Fan Circuit	Fan Terminal Strip
15	Empty		
16	White/Red	Fan Circuit	Fan Terminal Strip
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Fan Terminal Strip
23	Empty		
24	White/Black	Fan Circuit	Fan Terminal Strip
25	Empty		
26	Empty		
27	Empty		
28	Empty		
29	Empty		
30	Blue	Lamp 1 foot end	Capacitor 1-1
31	Yellow	Lamp 2 foot end	Capacitor 1-2
32	Orange	Lamp 3 foot end	Capacitor 1-3
33	Purple	Lamp 4 foot end	Capacitor 1-4
34	Grey	Lamp 5 foot end	Capacitor 1-5
35	Pink	Lamp 6 foot end	Capacitor 1-6
36	Tan	Lamp 7 foot end	Capacitor 1-7
37	Light Blue	Lamp 8 foot end	Capacitor 1-8

Lamp orientation is from FRONT of unit to BACK of unit (#1 through #16)

HARNESS CORD #2 / RECEPTACLE #2




PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 9 head end	Ballast 2-1
2	Yellow	Lamp 10 head end	Ballast 2-2
3	Orange	Lamp 11 head end	Ballast 2-3
4	Purple	Lamp 12 head end	Ballast 2-4
5	Grey	Lamp 13 head end	Ballast 2-5
6	Pink	Lamp 14 head end	Ballast 2-6
7	Tan	Lamp 15 head end	Ballast 2-7
8	Light Blue	Lamp 16 head end	Ballast 2-8
9	Empty		
10	Empty		
11	Empty		
12	Empty		
13	Empty		
14	Empty		
15	Empty		
16	White/Red	Fan Circuit	Fan Terminal Strip
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Fan Terminal Strip
23	Empty		
24	Empty		
25	Empty		
26	Empty		
27	Empty		
28	Empty		
29	Empty		
30	Blue	Lamp 9 foot end	Capacitor 2-1
31	Yellow	Lamp 10 foot end	Capacitor 2-2
32	Orange	Lamp 11 foot end	Capacitor 2-3
33	Purple	Lamp 12 foot end	Capacitor 2-4
34	Grey	Lamp 13 foot end	Capacitor 2-5
35	Pink	Lamp 14 foot end	Capacitor 2-6
36	Tan	Lamp 15 foot end	Capacitor 2-7
37	Light Blue	Lamp 16 foot end	Capacitor 2-8

Lamp orientation is from FRONT of unit to BACK of unit (#1 through #16)

134 SERIES AND 128 SERIES


HARNESS CORD #3 / RECEPTACLE #3



PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 1 head end	Ballast 3-1
2	Yellow	Lamp 2 head end	Ballast 3-2
3	Orange	Lamp 3 head end	Ballast 3-3
4	Purple	Lamp 4 head end	Ballast 3-4
5	Grey	Lamp 5 head end	Ballast 3-5
6	Pink	Lamp 6 head end	Ballast 3-6
7	Tan	Lamp 7 head end	Ballast 3-7
8	Light Blue	Lamp 8 head end	Ballast 3-8
9	White/Orange	Lamp 9 head end	Ballast 3-9
10	Red/Black*	Facial Ballast #1	Facial Ignitor #1
11	Empty		
12	Red/Yellow*	Facial Ballast #2	Facial Ignitor #2
13	Empty		
14	Red	Facial Fan	Facial Terminal Strip
15	Red/Green*	Facial Ballast #3	Facial Ignitor #3
16	White/Red	Fan Circuit Ballast	Fan Terminal Strip
17	Empty		
18	Red/White	Contactor Facial Control	Common on Flag Switch
19	Green	Ground	Ground
20	Black/White	Facial Timer Switch	Open Flag Switch
21	Empty		
22	Black	Fan Circuit	Fan Terminal Strip
23	Black/Red*	Facial Terminal Strip	Facial Ignitor #1
24	White/Black	Fan Circuit	Contactor-Fan
25	Black/Yellow*	Facial Terminal Strip	Facial Ignitor #2
26	Empty		
27	Black/Green*	Facial Terminal Strip	Facial Ignitor #3
28	Empty		
29	Blue	Lamp 1 foot end	Capacitor 3-1
30	Yellow	Lamp 2 foot end	Capacitor 3-2
31	Orange	Lamp 3 foot end	Capacitor 3-3
32	Purple	Lamp 4 foot end	Capacitor 3-4
33	Grey	Lamp 5 foot end	Capacitor 3-5
34	Pink	Lamp 6 foot end	Capacitor 3-6
35	Tan	Lamp 7 foot end	Capacitor 3-7
36	Light Blue	Lamp 8 foot end	Capacitor 3-8
37	White/Orange	Lamp 9 foot end	Capacitor 3-9

*If unit is equipped with Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #18)


HARNESS CORD #4 / RECEPTACLE #4



PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 10 head end	Ballast 4-1
2	Yellow	Lamp 11 head end	Ballast 4-2
3	Orange	Lamp 12 head end	Ballast 4-3
4	Purple	Lamp 13 head end	Ballast 4-4
5	Grey	Lamp 14 head end	Ballast 4-5
6	Pink	Lamp 15 head end	Ballast 4-6
7	Tan	Lamp 16 head end	Ballast 4-7
8	Light Blue	Lamp 17 head end	Ballast 4-8
9	White/Orange	Lamp 18 head end	Ballast 4-9
10	Empty		
11	Empty		
12	Empty		
13	Empty		
14	Empty		
15	Empty		
16	White/Red	Fan Circuit	Fan Terminal Strip
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Fan Terminal Strip
23	Empty		
24	Empty		
25	Empty		
26	Empty		
27	Empty		
28	Empty		
29	Blue	Lamp 10 foot end	Capacitor 4-1
30	Yellow	Lamp 11 foot end	Capacitor 4-2
31	Orange	Lamp 12 foot end	Capacitor 4-3
32	Purple	Lamp 13 foot end	Capacitor 4-4
33	Grey	Lamp 14 foot end	Capacitor 4-5
34	Pink	Lamp 15 foot end	Capacitor 4-6
35	Tan	Lamp 16 foot end	Capacitor 4-7
36	Light Blue	Lamp 17 foot end	Capacitor 4-8
37	White/Orange	Lamp 18 foot end	Capacitor 4-9


*If unit is equipped with Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #18)

134 & 128 SERIES WIRING DIAGRAM BALLAST BOX



134 & 128 SERIES WIRING DIAGRAM BALLAST BOX

REAR OF BALLAST BOX



FRONT OF BALLAST BOX

124 and 124/1 Bed Assembly and Wiring Diagrams


124 and 124/1

ASSEMBLY INSTRUCTIONS

TOOLS YOU WILL NEED:

- A. 9/16" SOCKET
- B. 7/16" SOCKET
- C. 1/4" ALLEN WRENCH (PROVIDED)
- D. 5/32" ALLEN WRENCH (PROVIDED)
- E. 13mm SOCKET OR ADJUSTABLE CRESCENT WRENCH
- F. TWO (2) OR MORE PEOPLE

STEP 1: POSITION THE BENCH UPSIDE DOWN. DETERMINE LEFT AND RIGHT LEGS BY POSITIONING THE SHOULDER BOLTS ON THE LEGS TO THE INSIDE AND FRONT OF THE UNIT. USING THE 1/4" - 20X 7/8 BOLTS AND 1/4" WASHERS PROVIDED AND BOLT THE LEGS TO THE BENCH.




(USING THE 7/16 SOCKET WRENCH).

STEP 2: TURN THE UNIT RIGHT SIDE UP, PLACE THE CANOPY ON THE TOP OF THE BENCH ALIGNING THE HINGE PLATES, BOLT THE HINGE PLATES TOGETHER USING THE 1/2" X 1/2" SHOULDER BOLT AND 3/8" NUT.

STEP 3: SNAP THE LARGE END OF THE SHOCK ONTO THE CANOPY LIFT THE CANOPY AND SNAP THE SMALL END ONTO THE BENCH.

NOTE: PROPER CANOPY ADJUSTMENT - IF CANOPY RAISES ON IT'S OWN, MOVE SHOCK ADJUSTMENT ON CANOPY TO REAR POSITION. IF CANOPY FALLS TO QUICKLY, MOVE SHOCK ADJUSTMENT ON CANOPY TO FORWARD POSITION.



STEP 4: PLACE THE BALLAST BOX BETWEEN THE LEGS OF THE UNIT. RUN CORD 1 FROM THE BENCH TO THE BALLAST BOX. RUN CORD 2 FROM THE CANOPY TO THE BALLAST BOX. PLACE THE FRONT FACADE ONTO THE FRONT OF THE UNIT.

WARNING: TO INSURE PROPER INSTALLATION OF CORDS, TIGHTEN CORDS UNTIL THEY LOCK.


NOTE: WEAR PROTECTIVE EYEWEAR: FAILURE TO DO SO MAY RESULT IN SEVERE BURNS OR LONG-TERM INJURY TO EYES.

NOTE: ELECTRICAL CONNECTION TO POWER SUPPLY MUST BE IN COMPLIANCE WITH NECA REGULATIONS AND PERFORMED BY A QUALIFIED ELECTRICIAN.

IF YOU HAVE ANY QUESTIONS, PLEASE CALL: 1-800-554-8268

124 SERIES


HARNESS CORD #1 / RECEPTACLE #1



PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 1 head end	Ballast 1-1
2	Yellow	Lamp 2 head end	Ballast 1-2
3	Orange	Lamp 3 head end	Ballast 1-3
4	Purple	Lamp 4 head end	Ballast 1-4
5	Grey	Lamp 5 head end	Ballast 1-5
6	Pink	Lamp 6 head end	Ballast 1-6
7	Tan	Lamp 7 head end	Ballast 1-7
8	Light Blue	Lamp 8 head end	Ballast 1-8
9	White/Orange	Lamp 9 head end	Ballast 1-9
10	White/Blue	Lamp 10 head end	Ballast 1-10
11	White/Green	Lamp 11 head end	Ballast 1-11
12	Black/Red	Lamp 12 head end	Ballast 1-12
13	Empty		
14	Red	Fan Circuit	Contactor-Fan
15	Empty		
16	White/Red	Fan Circuit	Contactor-Fan
17	Empty		
18	Empty		
19	Green	Ground	Ground
20	Empty		
21	Empty		
22	Black	Fan Circuit	Contactor-Fan
23	Empty		
24	White/Black	Fan Circuit	Contactor-Fan
25	Empty		
26	Blue	Lamp 1 foot end	Capacitor 1-1
27	Yellow	Lamp 2 foot end	Capacitor 1-2
28	Orange	Lamp 3 foot end	Capacitor 1-3
29	Purple	Lamp 4 foot end	Capacitor 1-4
30	Grey	Lamp 5 foot end	Capacitor 1-5
31	Pink	Lamp 6 foot end	Capacitor 1-6
32	Tan	Lamp 7 foot end	Capacitor 1-7
33	Light Blue	Lamp 8 foot end	Capacitor 1-8
34	White/Orange	Lamp 9 foot end	Capacitor 1-9
35	White/Blue	Lamp 10 foot end	Capacitor 1-10
36	White/Green	Lamp 11 foot end	Capacitor 1-11
37	Black/Red	Lamp 12 foot end	Capacitor 1-12

*If unit is equipped with Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #20)


HARNESS CORD #2 / RECEPTACLE #2




PIN#	COLOR	RECEPTACLE LOCATION	PLUG LOCATION
1	Blue	Lamp 1 head end	Ballast 2-1
2	Yellow	Lamp 2 head end	Ballast 2-2
3	Orange	Lamp 3 head end	Ballast 2-3
4	Purple	Lamp 4 head end	Ballast 2-4
5	Grey	Lamp 5 head end	Ballast 2-5
6	Pink	Lamp 6 head end	Ballast 2-6
7	Tan	Lamp 7 head end	Ballast 2-7
8	Light Blue	Lamp 8 head end	Ballast 2-8
9	White/Orange	Lamp 9 head end	Ballast 2-9
10	White/Blue	Lamp 10 head end	Ballast 2-10
11	White/Green	Lamp 11 head end	Ballast 2-11
12	Black/Red	Lamp 12 head end	Ballast 2-12
13	Empty		
14	Red*	Fan Term Strip	Facial Fan
15	Empty		
16	White/Red	Fan Circuit	Contactor-Fan
17	Red/Black*	Facial Ballast #1	Facial Ignitor
18	Red/White*	Facial Contactor Control	Facial Flag Switch
19	Green	Ground	Ground
20	Black/White*	Timer Board	Facial Flag Switch
21	Empty		
22	Black	Fan Circuit	Contactor-Fan
23	Empty		
24	White/Black*	Fan Term Strip	Facial Fan
25	Black/Red*	Facial Contactor	Facial Ignitor
26	Blue	Lamp 1 foot end	Capacitor 2-1
27	Yellow	Lamp 2 foot end	Capacitor 2-2
28	Orange	Lamp 3 foot end	Capacitor 2-3
29	Purple	Lamp 4 foot end	Capacitor 2-4
30	Grey	Lamp 5 foot end	Capacitor 2-5
31	Pink	Lamp 6 foot end	Capacitor 2-6
32	Tan	Lamp 7 foot end	Capacitor 2-7
33	Light Blue	Lamp 8 foot end	Capacitor 2-8
34	White/Orange	Lamp 9 foot end	Capacitor 2-9
35	White/Blue	Lamp 10 foot end	Capacitor 2-10
36	White/Green	Lamp 11 foot end	Capacitor 2-11
37	Black/Red	Lamp 12 foot end	Capacitor 2-12

*If unit is equipped with 1 Facial Cassettes
Lamp orientation is from FRONT of unit to BACK of unit (#1 through #20)


124 SERIES WIRING DIAGRAM BALLAST BOX



124 SERIES WIRING DIAGRAM BALLAST BOX



124 SERIES BALLAST BOX



LIMITED WARRANTY

Heartland Tanning, Inc. warrants its products to be free from defects in materials and workmanship under intended normal use as described in the unit's Operation and Instruction Manual, for a period of three (3) years from date of sale.

This Limited Warranty applies only to the original purchaser of the equipment through Heartland Tanning, Inc. or its authorized dealer or distributor, and is not transferable.

Heartland Tanning, Inc.'s obligations under this warranty are limited to repair or replacement of any defective part without charge for that part to the original purchaser, with the following exceptions:

- A. Tanning lamps are warranted against defects for a period of sixty (60) days from date of sale.
- B. Three (3) year Limited Warranty on parts. Only parts obtained through Heartland Tanning, Inc., its authorized dealers or distributors may be used. Transportation cost for parts shipped to the consumer and the return of defective parts to Heartland Tanning, Inc. are not included.
- C. Labor will be furnished without charge for ninety (90) days from the date of purchase only. All labor and related charges must be authorized by Heartland Tanning, Inc. prior to start of repairs, and must coincide with Heartland Tanning, Inc. established rates and time allotment policy.
- D. All fans are warranted against defects for a period of three (3) years from date of sale.
- E. Timer system warranted for one (1) year.
- F. Acrylic, warranted for twelve (12) months.
- G. Shocks warranted for ninety (90) days.

It is imperative that the original customer completes and returns the enclosed warranty card within ten (10) days after purchase to insure valid registration and coverage for potential claims.

If the warranty card is not registered, proof of purchase from Heartland Tanning, Inc. or its authorized dealer or distributor will be required prior to any consideration on warranty claims. This could result in service delays.

This warranty is extended to the individual or legal entity, whose name appears on the warranty registration card filed with Heartland Tanning, Inc., or whose name appears on the original sale document and may not be transferred to any other individual or legal entity.

This warranty does not apply to any failure of the product or any parts of the product due to alterations, modifications, misuse, abuse, accident, improper maintenance, improper installation or if the serial number on the product has been removed, altered, or defaced. Adequate packaging must be used for returned goods to prevent freight damage.

THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND HEARTLAND TANNING, INC. NO PERSON, FIRM OR CORPORATION IS AUTHORIZED TO OBLIGATE HEARTLAND TANNING, INC. FOR ANY LIABILITY IN CONNECTION WITH THE SALE OR USE OF THESE GOODS.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

NOTICE: Any misuse, abuse, modifications, alteration, improper installation, etc. of this product or its intended use will subject said party to direct responsibility for any and all consequences resulting from such action. Furthermore, such actions will void all warranties and may relieve Heartland Tanning, Inc. of any liabilities relating to said product.